

CABLES AMRCA DIVISION

June 7, 2014

Class	Class	Color	Present Cable	Change Speed / Next Cable
Class 1	(Manufactured)	Yellow	.055 in. (1.4mm)	157 MPH / .059 in.
Class 2 A-B	(Manufactured Modified)	Yellow	.055 in. (1.4mm)	157 MPH / .059 in.
Class 3 A	(Custom Open)	Red	.063 in. (1.6mm)	177 MPH / .067 in.
Class 3 B	(Custom Side Exhaust)	Purple	.059 in. (1.5mm)	167 MPH / .063 in.
Class 3 C	(Custom Fully Suspended)	Red	.063 in. (1.6mm)	177 MPH / .067 in.
Class 4	(Manufactured Proto B Grade)	Yellow	.055 in. (1.4mm)	157 MPH / .059 in.
Class 5 A	(Experimental Open)	Blue	.067 in. (1.7mm)	187 MPH / .071 in.
Class 5 B	(Experimental Unlimited)	Orange	.071 in. (1.8mm)	198 MPH / .075 in.
Class 5 C	(Experimental Unlimited Unpipied)	Orange	.071 in. (1.8mm)	198 MPH / .075 in.
Class 6 A	(Modified Mite Up to .129 c.i.)	White	.035 in. (.9 mm)	137 MPH / .047 in.
Class 6 B	(Modified Mite .13 to .159 c.i.)	White	.035 in. (.9 mm)	137 MPH / .047 in.
Class 6 C	(Modified Mite .16 to .219 c.i.)	White	.035 in. (.9 mm)	129 MPH / .047 in.
Class 6 D	(Modified Mite .22 to .299 c.i.)	Green	.047 in. (1.2 mm)	160 MPH / .055 in.
Class 7 A	(Stock Mite Up to .099 c.i.)	White	.035 in. (.9 mm)	137 MPH / .047 in.
Class 7 B	(Stock Mite .10 to .159 c.i.)	White	.035 in. (.9 mm)	137 MPH / .047 in.
Class 7 C	(Stock Mite .16 to .199 c.i.)	White	.035 in. (.9 mm)	129 MPH / .047 in.
Class 7 D	(Stock Mite .20 to .299 c.i.)	Green	.047 in. (1.2 mm)	160 MPH / .055 in.
Class 8	(Spur gear)	Yellow	.055 in. (1.4mm)	157 MPH / .059 in.
Class 9 A-B	(Modern Nostalgia 46 + 60)	Yellow	.055 in. (1.4mm)	157 MPH / .059 in.
Class 10 A	(Front Intake Custom 46)	Yellow	.055 in. (1.4mm)	157 MPH / .059 in.
Class 10 B	(Front Intake Custom 60)	Purple	.059 in. (1.5mm)	167 MPH / .063 in.